

INDUSTRIAL SOLENOID VALVE



Specification

- Model No. : 2W SLD NV66
- Pipe Size : ½" to 1"
- Body Material : Nylon
- Seal Material : NBR
- Pressure Range : 0 to 6 Bar
- Operating Voltage : 230v AC , 24v DC, 12v DC

SEMI LIFT DIAPHRAGM SOLENOID VALVE



Specification

- **Model No.** : 2W SLD CF8
- **Pipe Size** : ½" to 2"
- **Body Material** : CF8
- **Seal Material** : NBR / VITON / EPDM
- **Pressure Range** : 0 to 6 Bar
- **Operating Voltage** : 230v AC , 24v DC, 12v DC

SEMI LIFT DIAPHRAGM SOLENOID VALVE



Specification

- **Model No.** : 2W SDA
- **Pipe Size** : 1/8" to 1/2"
- **Body Material** : SS304 / BRASS / ALUMINIUM
- **Seal Material** : NBR
- **Pressure Range** : 0 to 10 Bar
- **Operating Voltage** : 230v AC , 24v DC, 12v DC

**DIRECT
ACTING
SOLENOID VALVE**



Specification

- Model No. : 2W POD CF8
- Pipe Size : ½" to 2"
- Body Material : Cf8
- Seal Material : NBR / VITON / EPDM
- Pressure Range : 0.5 to 12 Bar
- Operating Voltage : 230v AC , 24v DC, 12v DC

PILOT OPERATED DIAPHRAGM SOLENOID VALVE



Specification

- **Model No.** : 2W ADC
- **Pipe Size** : 1" to 1 ½ "
- **Body Material** : ALUMINIUM DIE CAST
- **Seal Material** : NBR
- **Pressure Range** : 0.5 to 8 Bar
- **Operating Voltage** : 230v AC , 24v DC, 12v DC

**DUST
COLLECTOR
VALVE**



Specification

- **Model No.** : 2W YSC / YFC
- **Pipe Size** : ½" to 2"
- **Body Material** : Cf8
- **Seal Material** : PTFE
- **Pressure Range** : 10 Bar
- **Actuator** : PNEUMATIC

Y TYPE PNEUMATIC CONTROL VALVE

